



Print & Apply Labeler with Intelligent Motion<sup>™</sup> technology

# Videojet® 9560 Corner Wrap

The Videojet 9560 Corner Wrap is a smarter print and apply labeler that is designed to target zero unscheduled downtime and can help reduce costs and errors in case coding operations.

Our Intelligent Motion<sup>™</sup> technology automatically and precisely controls the entire system, helping to remove operational downtime often caused by label jams and snagged labels. A robust and simply designed applicator makes it easy to use, plus an integrated pack detect feature helps ensure accurate label placement.

The 9560 with Corner Wrap applicator is ideal for cases or shrink wrapped products where the label must be applied across adjacent panels so that label information can be seen in various orientations.



## Industry-proven labeling technology

- Optimize maintenance labor by removing common wear and adjustment parts
- Built in pack/case detect sensor eliminates the need for additional components, simplifying integration and set-up
- Clean, robust design helps protect components during operation
- Eliminate label jams for common top or side labeling applications

## Remove end-of-line inefficiencies

- Intelligent Motion<sup>™</sup> technology delivers automatic control of the system and eliminates the added parts and adjustments that can make other labeling machines fail
- A direct drive controls label speed and position without clutches, rollers or adjustments
- Electronic supply reel automatically adjusts and maintains tension irrespective of speed and label size

### Seamless connectivity and compatibility

- Virtually eliminate operator errors, helping to ensure products are coded correctly with built-in Code Assurance software features
- Includes embedded Wi-Fi for secure remote access and analytical capabilities
- Intelligent emulation capabilities include EtherNet/IP<sup>™</sup>, PROFINET<sup>®</sup>, Zebra, SATO and CoLOS protocols

## Simple usability

- Perform label and ribbon changes in less than 60 seconds
- Single simple 8-inch user interface for easy control
- Onboard support videos guide the operator through routine tasks
- Flexibility to position user interface remotely
- Ability to access the interface on a connected network, including via mobile devices

## Videojet<sup>®</sup> 9560 Corner Wrap

## Print & Apply Labeler with Intelligent Motion<sup>™</sup>technology

#### Application method

Direct Apply™ technology for side panel, pneumatic roller wipe for rear panel

#### Print technology

Thermal transfer printing with Intelligent Motion™ Ribbon Drive and Direct Thermal 53mm, 76mm and 107mm printhead versions

#### **Print resolution**

300dpi / 200dpi emulation mode

#### Printhead health monitoring

Tool-free quick release printhead replacement

#### Print speed

1.6 – 19.7 inches/sec (40 – 500 mm/sec)

#### Throughput

Up to 48 packs per minute (depending on label size) Recommended max conveyor speed 98.4ft/min (30m/min)

#### **Ribbon specification**

Width: 2.2" (55mm), 3.0" (76mm) and 4.3" (110mm) standard Capacity: Up to 830m, including automatic ribbon save (<1mm ribbon gap between successive prints irrespective of label size or speed) Low Ribbon/End of Ribbon detection with predicted changeover time built in as standard

#### Label specification

Label Width 1.6" to 4.5" (40mm to 115mm); dependent on printhead version Label Length 2.0" to 11.8" (50mm to 300mm)

Capacity: Up to 400mm spool diameter (typically delivers over 9000 typical GS1 bar code labels per roll)

Low Labels and End of Label Reel detection, with predicted changeover time built in as standard Automatic adjustment for label/backing type and label size

#### **Print capabilities**

Full downloadable font support using TrueType® fonts (including multiple languages and Unicode support); fixed, variable and merged text fields; flexible date/time formats; flexible shift code formats; auto best before date calculations and concession management; calendar rules; auto incrementing decrementing text, counters and bar codes; multiple graphic formats supported (up to maximum print area); link fields to databases; scalable text and text blocks; 1GB on-board label database, sufficient for 62,000 typical GS1 bar code label designs

#### Bar codes supported

EAN 8, EAN 13, UPC-A, UPC-E, Code 39, GS1-128, Code 128, ITF, RSS (including 2D composite codes); others available upon request

#### Connectivity

Ethernet, Power-over-Ethernet, RS232, Configurable I/O (24V, PNP and volt free) USB (backup/restore and label upload), remote control Videojet 9560 via a web browser

#### **Communications Protocols**

Compatible with Videojet CLARiSUITE™

Videojet binary and simple-ASCII protocols

Compatible with any label design software which supports Zebra or Sato print engines Zebra (ZPL), Sato (SBPL) and Markem-Imaje (Cimcomms) protocol support EtherNet/IP<sup>TM</sup>

**PROFINET**®

#### Need labels for your label applicator?

Marsh Label Technologies provides standard, specialty, and custom labeling solutions. A Videojet affiliate company, **Marsh** works directly with Videojet in testing and qualifying label materials to provide maximum performance for 9560 Print and Apply users.

Contact info: info@marshlabel.com / (800) 975-3444

#### New printer quote 866-871-3226

Order supplies **shop.videojet.com** Call **800-843-3610** Email **info@videojet.com** or visit **www.videojet.com** 

Videojet Technologies Inc. 1500 Mittel Blvd. Wood Dale IL 60191 / USA Interface

CLARiTY™ Controller with interactive on-board video tutorials

#### Language Capabilities

Arabic, Bulgarian, Czech, Danish, English, German, Greek, Finnish, French, Hebrew, Hungarian, Italian, Japanese, Korean, Dutch, Norwegian, Polish, Portuguese, Romanian, Russian, Serbian, simplified Chinese, Slovak, Spanish, Swedish, Thai, Turkish, Traditional Chinese, Vietnamese

#### **Compressed Air**

6 Bar. 90psi, uncontaminated

#### Power Consumption

90-260 VAC (115W at 50 packs per minute)

#### **Operating Environment**


Temperature Range: 41-104°F (5-40°C) Humidity: 20-85% Relative, non-condensing

#### Weight

Corner Wrap applicator – 15.20lbs (7kg) 9560 excluding ribbon and labels – max 88.19lbs (40kg)

#### Applicable certifications

CE, TüV



©2024 Videojet Technologies Inc. — All rights reserved.

Videojet Technologies Inc.'s policy is one of continued product improvement. We reserve the right to alter design and/or specifications without notice. TrueType is a registered trademark of Apple Computer, Inc.

Part No. SL000732 ss-9560-corner-wrap-us-0724 Printed in U.S.A.

